

People Make the Difference

RMD Kwikform is a powerfu mprising the skill nd energy o









Our Experience & Expertise

Kwikstage is one of the most universally established scaffolds throughout the world. Used for propping and decking applications, it's the inherent simplicity that makes Kwikstage a versatile, efficient and cost effective alternative to traditional loose props.

It's the result of over 50 years experience gained on major projects throughout the world. What's more, our network of local branches means when you deal with RMD Kwikform, you talk to people who understand the working environment, technical difficulties and challenges you face.













Applications

Kwikstage propping and decking is a highly versatile, competitive slab formwork system capable of being used in many applications including:

- **Commercial buildings**
- **Shopping malls**
- High rise residential apartments
- Airport terminals
- Light industrial slabs
- Bridge Decks



INTRODUCTION



Clien Al Habtoor Murray Roberts J

Proje Madinat Jumeirah Dubai, UAR



Client: Khansaheb Civil Engineering L.L.C..

Project: Wafi Centre, Dubai, UAE.





Project: Saudi Al Khodari

Features & Benefits

- **Quick striking system**, enabling early removal of deck beams and plywood, saving time and cost.
- Variable ledger positions to suit leg loading, increasing flexibility of the system.
- Make-up areas around columns can be supported simply by using infill beams, saving customer time and money.
- Braces fit to the standards using half couplers ensuring no loose parts, minimising loss and damage charges.



Client: Cebarco WCT JV. **Project:** City Centre Hotel, Bahrain. Quick and easy to erect propping ties are fixed to the vertical standards using captive wedge connections, saving time.

- **Simple erection procedure** ensures stringent safety levels can be easily achieved.
- As an alternative to steel decking and infill beams, Kwikstage Propping can also be used in conjunction with RMD Kwikform's GTX and aluminium beams for soffit support to slabs of all depths.



recht, TAV & CCC JV



Client: Nass Burhan JV. Project: King Hamad Hospital,



FEATURES & BENEFITS

FEATURES & BENEFITS





Client: Al-Enmma Real Estimating Co.

Project: Al Asffour Tower, Kuwait City, Kuwait

Standards - Open Ended

Code	Length (m)	Weight (Kg)
KPX31000	0.99	5.2
KPX31500	1.49	7.8
KPX32000	1.98	10.4
KPX32500	2.49	13.0
KPX33000	2.97	15.62



Propping Ties

495m

- 🔻

Code	Centres of standards (m)	O/A Length (m)	Weight (Kg)
KPX42400	2.4	2.35	9.1
KPX41800	1.8	1.75	7.0
KPX41200	1.2	1.15	4.8
KPX40900	0.9	0.85	3.8
KPX40600	0.6	0.55	2.7



Coupler Braces

Code	Length O/A (m)	Length C/C (m)	V (m)	H (m)	Weight (Kg)
KPX51470	1.47	1.40	1.00	1.20	6.2
KPX51790	1.76	1.70	1.50	1.20	7.3
KPX52170	2.17	2.10	2.00	1.20	8.3
KPX52170	2.17	2.10	1.50	1.80	8.3
KPX52170	2.17	2.10	1.00	1.80	8.3
KPX52560	2.56	2.50	1.00	2.40	10.1
KPX52560	2.56	2.50	2.00	1.80	10.1
KPX52730	2.73	2.67	1.50	2.40	10.7
KPX53030	3.03	2.97	2.00	2.40	11.8



Flanged Spigot Adaptor





Drophead Code Max axial load Weight (Kg) (kN) KPX80001 40 6.13 667mm 760mm Adjustable Base Jack Code Description Weight (Kg) KPM00014 Adjustable Base Jack 3.9 Range = 40 - 610mm • KPX20002 HD Adjustable Base 5.5



Infill Beams

Code	Length to centres of supports (m)	Weight (Kg)
KPX70120	1.2	5.51
KPX70900	0.9	4.13
KPX70600	0.6	2.73

antilever Deck Beam		
Code	Description	Weight (Kg)
KPM00020	Cantilever Deck Beam	3.8



Code	Description	Weight (Kg)
KPX80009	Drophead Extension	2.2

COMPONENTS

5

COMPONENTS



KPM00008	5	1.0

Internal	Poom F	rackat	
Internal	Beam E	racket	
Internal ^{Code}	Beam E W (m)	Bracket H (m)	Weight (Kg)
Internal Code KPX11000	Beam E W (m) 0.2	Bracket H (m)	Weight (Kg) 5.8





Decking Beams

Code	Grid Centres (m)	'A' (m)	Weight (Kg)
KPX72400	2.4	0.622	22.8
KPX71800	1.8	0.470	17.5
KPX71200	1.2	-	9.5
KPX70901	0.9	-	7.57

Erection Procedure



Two operatives place open ended standards over base jacks that have been pre-adjusted to approximately the correct height.

The operators then hold the standards/bases vertical and insert a ledger/propping tie into the lowest set of pressings on the standard (they do not fully tighten the captive wedges at this point).



Continue erecting the lower standards in a similar way adding bracing as required by the RMD Kwikform Drawing.



Working from the boarded platform, adjust the Adjustable U-Heads to approximate required jack extension and insert into the top level of open ended standards.



The operatives lean the constructed frame inwards and, whilst holding it with one hand, attach propping ties into the first set of pressings at the bottom of the standard. The frame is now self supporting.



The operatives each prepare another leg (standard & base) and connect these to the free ends of propping ties protruding from the initial frame.



Once the bottom lift is complete, place scaffold boards on the top propping tie (using intermediate board supports where required) to provide a platform to erect the next level of standards.



Working from the established boarded platform, insert primary beams into the centre of the U-Head. Twist the U-Head and insert wedges to ensure the primary beams are central.



The first unit of the grid is completed by tying the legs to one another with propping ties to the required set of pressings on the standards and leveling-off and squaring up. Once this is completed, wedges are hammered up tight. Always refer to RMD Kwikform design drawing.



At all times operatives should comply with local safety regulations by either using approved fall arrest equipment or by providing temporary guardrails as shown.

Continue erecting remaining levels of standards and propping ties in accordance with the RMD Kwikform drawing.



Erect the secondary beams and fix to the Primary Beams using a minimum of 2 GTX Cleats per secondary beam.

ERECTION PROCEDURE

5

Place diagonal bracing to the tower as required by the RMD Kwikform drawing. Ensure the tower is vertical and square prior to tightening the couplers.



Move or extend the working platform to the remaining areas and erect upper levels of standards and propping ties.



Place the plywood and secure to secondary beams using suitable screws or nails. Erect perimeter guardrails and toe boards to comply with local safety regulations.

Loading Data

Kwikstage, scaffolding with 'Propping ties' is suitable for support applications with 27.5kN leg loading when the vertical dimensions between the horizontal members is at a maximum of 2m vertical centres. The leg load can be increased to 40kN when the maximum vertical distance between the horizontal members is limited to 1.5m, and 55kN leg load can be accommodated when the horizontal members are at 1.0m vertical centres.

Wherever Kwikstage scaffolding is used for support, bracing will be necessary to provide lateral stability, overall stability, erection stability and node point stability for the effective length of standards. Installing one bracing pattern often provides sufficient bracing to cover the other cases. The design of bracing and the horizontal restraint force required to be transmitted through the braces is specified in BS 5975: 2008 'Falsework'.

Where head fixity can be guaranteed through the plywood decking restraining the head of the system between columns and/or walls, then bracing for 1% of the vertical load in all standards may be used in the design of the jacks (provided the columns and walls can restrain these loads).

BS5975 specifies a minimum lateral stability criteria equivalent to the greater of either: 2.5% of the vertical load in the standards acting horizontally at the point of application of the load, or horizontal forces from wind, erection tolerances, non vertically, concrete pressures and other forces acting as described in the code. The SWL of a coupler brace is 6.25kN, this being the slip capacity of the connection in tension or compression. The requirement to brace the head and base jacks will depend on their individual extensions and the load being carried, as detailed below.

It is assumed standards are connected by ledgers and braced between the uppermost and lowest node points and all nodes in between.

Kwikstage Code KPM00017 Adjustable 'U' Head Jack Loading Graph.

Unbraced Condition (300mm from end of Standard to first node).



Kwikstage Code KPM00014 Adjustable Base Jack Allowable Loading Graph. Unbraced Condition (200mm from end of Standard to first node).



Safe Working Loads for Decking Beams

The decking beams span between dropheads or between decking beams running in the opposite direction. The system is designed to support a load of 40kN on any bay. This therefore gives a max load on any supporting leg of 40kN. This can be equated to a slab thickness

Grid Centres (m)	O/A Length (m)	SWL (kN) (UDL)	SWL (kN) Point Load on Node(s)
2.4	2.28	40	10
1.8	1.68	40	10
1.2	1.08	40	20

Loads applied

concentrically

Jack Extension

300mm

Ledger on highest node

Ledger on lowest node

200mm

Jack Extension

Lacing & Bracing Details



Diagonal Bracing - 27.5kN Capacity (@2.5% of the Vertical Load)

Bay Size (mm)	Code	No. of Bays per Brace	Lift Height (m)
2400	KPX53030	7	2.0
1800	KPX52560	7	2.0
1200	KPX52170	6	2.0



Diagonal Bracing - 40kN Capacity (@2.5% of the Vertical Load)

Bay Size (mm)	Code	No. of Bays per Brace	Lift Height (m)
2400	KPX52730	5	1.5
1800	KPX52170	5	1.5
1200	KPX51790	5	1.5



Diagonal Bracing - 55kN Capacity (@2.5% of the Vertical Load)

Bay Size (mm)	Code	No. of Bays per Brace	Lift Height (m)
2400	KPX52560	4	1.0
1800	KPX52170	4	1.0
1200	KPX51470	4	1.0

Note: Concrete w	Concrete Slab Thickness (mm)	irid Size (m)
accordance with For further inforr Technical Office.	459	.4 x 1.2
	290	.4 x 1.8
	198	.4 x 2.4
	627	.8 x 1.2
	403	.8 x 1.8
	991	.2 x 1.2

TECHNICAL

TECHNICAL





ight, decking self weight and superimposed load assumed in



middle east offices

UAE

Sharjah (ME Head Office) RMD Kwikform Middle East L.L.C., PO Box 5801, Sharjah, United Arab Emirates. Tel: +971 6 553 4173 Fax: +971 6 553 4327 Email: rmd.uae@rmdkwikform.com

Abu Dhabi

RMD Kwikform Middle East L.L.C., PO Box 259, Abu Dhabi, United Arab Emirates. Tel: +971 2 550 2383 Fax: +971 2 550 2384 Email: rmd.abudhabi@rmdkwikform.com

Dubai

RMD Kwikform Middle East L.L.C., P.O. Box 115480, Dubai, United Arab Emirates. Tel: +971 4 885 6144 Fax: +971 4 885 6141 Email: rmd.dubai@rmdkwikform.com

Bahrain

RMD Kwikform Bahrain W.L.L., PO Box 21475, Flat 12, Building 829, Road 833, Block 408, Sanabis, Bahrain. Tel: +973 1738 2724 Fax: +973 1738 2624 Email: rmd.bahrain@rmdkwikform.com

Lebanon

RMD Kwikform, PO Box 16-7115, Atco - Hazmieh, 3rd Floor, Hobeika Centre, Beirut, Lebanon. Tel: +961 545 0214 Fax: +961 545 5387 Email: rmd.lebanon@rmdkwikform.com

Oman

RMD Kwikform Oman L.L.C., PO Box 889, Post Code 100, Muscat, Sultanate of Oman. Tel: +968 2449 6037 Fax: +968 2449 5836 Email: rmd.oman@rmdkwikform.com

Kuwait

RMD Kwikform, PO Box 42094, Shuwaik 70651, Kuwait. Tel: +965 484 5161 Fax: +965 484 6414 Email: rmd.kuwait@rmdkwikform.com

Saudi Arabia

Al Khobar RMD Kwikform Saudi Arabia L.L.C., Al-Bandariyah Centre, Office No 611 (Unit 5), Building No 3194, Prince Faisal Bin Fahad Road, Al Khobar 34424 - 8555, Saudi Arabia. Tel: +966 3 882 5444 Fax: +966 3 882 6460 Email: rmd.ksa@rmdkwikform.com

Jeddah

RMD Kwikform Saudi Arabia L.L.C., 3rd Floor, Al Rajhi Centre, Al Andalus Street (opp SACO), Jeddah, Kingdom of Saudi Arabia Tel: +966 2 664 8155 Fax: +966 2 664 8630 Email: rmd.ksa@rmdkwikform.com

Qatar

RMD Kwikform Qatar W.L.L., PO Box 405, Doha, Qatar. Tel: +974 465 3034 Fax: +974 465 3282 Email: rmd.qatar@rmdkwikform.com

european offices

United Kingdom

RMD Kwikform, Brickyard Road, Aldridge, Walsall WS9 88W, UK. Tel: +44 1922 743743 Fax: +44 1922 743400 Email: info@rmdkwikform.com

Ireland

RMD Kwikform, Ballyboggan Road, Finglas, Dublin 11, Ireland. Tel: +353 1 830 2500 Fax: +353 1 830 2522 Email: rmd.dublin@rmdkwikform.com

Portugal

RMD Kwikform, Av 24 de Abril, 32-a Esquerdo, 2870-150 Montijo, Portugal. Tel: +35 1 21 232 8688 Fax: +351 21 231 5715 Email: rmd.lisboa@rmdkwikform.com

Spain

RMD Kwikform Ibérica SA, Paseo del Club Deportivo, 1 Urbanización La Finca, Edif. 3, 1º Izda. 28223 Pozuelo de Alarcón, Madrid. Tel: +34 91 555 6104 Fax: +34 91 555 4745 Email: rmd.madrid@rmdkwikform.com

south america office

Chile

RMD Kwikform, Las Esteras 811, Lampa, Santiago, Chile. Tel: +56 2 714 9800 Fax: +56 2 747 2016 Email: rmd.chile@rmdkwikform.com

south africa office

South Africa

RMD Kwikform South Africa (PTY) Ltd, 52 Jakaranda Ave, Hennopspark, Centurion, Pretoria, South Africa. Tel: +27 12 681 0360 Fax: +27 12 681 0361 Email: rmd.sa@rmdkwikform.com

asia pacific offices

Australia RMD (Australia) Pty. Ltd. PO Box 169, Melrose Park, South Australia, 5039. Tel: +61 8 8179 8200 Fax: +61 8 8179 8201 Email: rmd.australia@rmdformwork.com

Hong Kong

RMD Kwikform, 22nd Floor Easy Tower, 609 Tai Nan West Street, Cheung Sha Wan, Kowloon, Hong Kong. Tel: +852 2415 4882 Fax: +852 2413 4797 Email: rmd.hongkong@rmdkwikform.com

Korea

RMD Kwikform Co. Ltd, 2nd Floor HO Building, 38-16 Jam Won-Dong, Seocho-Gu, Seoul, Korea. Tel: +82 2 545 2484 Fax: +82 2 545 1878 Email: rmd.seoul@rmdkwikform.com

New Zealand

RMD (New Zealand) Ltd. PO Box 22-316, 101-105 Station Road, Otahuhu, Auckland 6, New Zealand. Tel: +64 9 276 5955 Fax: +64 9 276 6732 Email: rmd.auckland@rmdformwork.com

Philippines

RMD Kwikform, Unit 1102, Annapolis Wilshire Plaza, #11 Annapolis Street, Greenhills, San Juan, Metro Manila, Philippines. Tel: +632 724 4213 Fax: +632 724 4214 Email: rmd.manila@rmdkwikform.com

Our policy is one of continuous improvement and we reserve the right to change, alter or modify any detail, design, weight, dimension or code without prior notice being given.

www.rmdkwikform.com

A member of Interserve Plc.

Kwikstage Propping - Issued March 2010